



Limited-Slip Axle Additive Concentrate

Kendall® Limited-Slip Axle Additive Concentrate is a special additive used to modify the frictional characteristics of axle lubricants for use in limited-slip differentials. It helps to eliminate chatter in limited-slip differentials when added to non-limited-slip API GL-5 gear lubricants.

Supplemental Friction Modifier for API GL-5 Gear Lubricants

Applications

Limited-Slip Axle Additive Concentrate is recommended for use with non-limited-slip API GL-5 gear lubricants to eliminate chatter in limited-slip differentials. The recommended mixing ratio is one fluid ounce of Limited-Slip Axle Additive Concentrate to one pint of API GL-5 gear lubricant.

Limited-Slip Axle Additive Concentrate meets the requirements of:

- Chrysler MS-5630
- Dana 40819
- Ford EST-M2C118-A

Features/Benefits

- Helps prevent chatter in limited-slip and positraction differentials

Limited-Slip Axle Additive Concentrate

Typical Properties	
Specific Gravity @ 60°F	0.912
Density, lbs/gal @ 60°F	7.59
Flash Point (COC), °C (°F)	>149 (>300)
Pour Point, °C (°F)	<-40 (<-40)
Viscosity, Kinematic	
cSt @ 100°C	9.2
SUS @ 210°F	57.0

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/SDS>

Updated: 05-26-2022